

AKUA**KARE**

Su Ürünleri İmalat İth. İht. Tic. Ltd. Şti.

FLOWMETERS



KFM SERIES ELECTROMAGNETIC FLOWMETERS

Thread, Flanged, Clamp Connections
Different Liner Materials and Electrodes
Remote or Local Display
High Measuring Accuracy, Quick Response Time
Analog and Digital Output, HART Protocol
CE and Wras Approved
Turkish and English Language

VM SERIES ELECTROMAGNETIC FLOWMETERS

Thread Connection
316Ti or PVDF Connection Options
Standard Pulse Output, Optional 4-20mA or 0-10 V
Compact Type for Filling Systems





TDS100 SERIES ULTRASONIC FLOWMETERS

Connection on Pipe Surface Quick Installation Types of Hand Held, Wall Mount, Modular Pipe Measure Range: DN15 ... DN6000

CG SERIES CORIOLIS MASS FLOWMETER

Thread, Flanged Clamp Connections
Remote or Local Display
High Measuring Accuracy, Quick Response Time
Quick Response Time
Analog and Digital Output HART Protocol

Measurement Accuracy: Gas: % 0,5, Liquid: % 0,2







AKUAKARE

Su Ürünleri İmalat İth. İht. Tic. Ltd. Şti.

FLOWMETERS



KF-500 SERIES URBINE TYPE FLOWMETERS

Thread, Flanged, Clamp Connections 304SS or PTFE Body Measurement Accuracy: % 1 Standart Pulse Output, Optional Display and Analog Output

OM SERIES OVALGEAR FLOWMETERS

Thread, Flanged, Clamp Connections
Aluminum or SS Body Options
Measurement Accuracy: % 0,5
Types of Low Flow Range, High Pressure
Standart Pulse Output, Optional Display and Analog Output
Ex-Proof and ATEX Approved





PLASTIC TUBE VARIABLE AREA FLOWMETERS

Models of Line Type, Pano Type
Glue or Thread Connection Options
Models of Different Pressure and Temp. Resistant
Types of Low and High Alarm Output

GLASS TUBE VARIABLE AREA FLOWMETERS

Models of Line Type, Pano Type
Thread, Flanged, Clamp Connection Options
Models of Different Pressure and Temp. Resistant
Types of Low and High Alarm Output
Types of Calibrated according to Operation Conditions







AKUAKARE

Su Ürünleri İmalat İth. İht. Tic. Ltd. Şti.

FLOWMETERS



LUG SERIES VORTEX FLOWMETER

Flanged or Wafer Type Connections
Remote or Local Display
High Measuring Accuracy, Quick Response Time
Analog and Digital Output, HART Protocol
Measurement Accuracy: % 1
Operation Condition: -40 ... + 350 °C
Temperature-Pressure Compansation

KF 800 SERIES METAL TUBE FLOWMETERS

Thread, Flanged Connection Options

Models of Different Pressure and Temp. Resistant

Types of Low and High Alarm Output


Analog Output and Digital Display Options Types of Calibrated according to Operation Conditions





MJ-SDC SERIES WATER METERS

Thread, Flanged Connection Options Types of Pulse Output Brass Iron Body



Line Type or Insertion Type Brass or SS Body Options Normally Open or Close Contact Different Connection Sizes









FLOW INDICATOR AND CONTROL PANELS

Pano Type Flow Indicators
Instat and Total Flow Indicators
24 Vdc or 220 Vac Power Supply
Effective Solutions for All Kinds of Fluids