

Omega Type Schackle - Screwed (GM 209) & Nutted (GM 2130)											
Nominal	Breaking	Measurements							Weight		Test
Mea.	Load	d	D	e	E	K	S	W	(Kg/pcs)		Load
(Inch)	Ton								Screwed	Nutted	Ton
5/8.	3,25	16	19	38	39	20,9	57	27	0,71	0,8	6,5
3/4.	4,75	19,5	22	44	48	24,2	65	31,5	1,14	1,29	9,5
7/8.	6,5	22,4	25	50	55	27,5	76	36,5	1,72	1,81	13
1	8,5	26	28	56	64	30,8	88	43	2,45	2,74	9
1-1/8.	9,5	30	32	64	70	35,2	101	46,5	3,49	3,88	19
1-1/4.	12	33	35	70	78	38,5	108	51,5	4,81	5,34	24
1-3/8.	13,5	37	38	76	85	41,8	126	57	6,28	6,78	27
1-1/2.	17	41	42	84	94	46,2	139	60	8,31	9,12	34
1-3/4.	25	48	51	100	119	56,1	168	74	15,2	16,33	50
2	35	54	60	122	146	66	202	83	21,47	22,52	70
2-1/2.	55	70	80	150	185	88	267	105	44,8	45,9	110
3	85	80	90	170	200	99	330	130	77,5	78	170
3-1/2.	120	95	110	210	230	121	360	140	131,3	132	240
4	150	108	125	240	260	137	380	150	157,8	160	300

